


Declaration of performance: Classic Red

Nr: YL001/03

1. Product definition	Category 1 fired brick for indoors and outdoors use
2. Product standard	In walls, columns and partitions according to SFS-EN 771-1:2011+A1:2015
3. Producer	Ylivieskan Tiili Oy, Lentokentäntie 833, 84880 Ylivieska, FINLAND
5. AVCP-procedure	AVCP 2+
6. Harmonized standard	EN 771-1:2011+A1:2015 Approved and audited by Inspecta Sertifiointi Oy (0416) certification nr. 0416-CPR-5907

7. Performance

Water absorption	max 20 %	
Initial rate of water	max 5,0 kg/m ² /min	
Bond strength	≥ 0,16 N/mm ² (Weber M5-mortar)	
Reaction to fire	Euro A1	
Frost durability	SFS7001, 4.1 Annex 1, method 1 (25 cycles)	
Product shape	Vertically perforated Group 2	
Vapour permeability	5/10 EN 1748	

Dimensions	Nominal dimension			Tolerance T1			Variation R1			Thermal conductivity EN1745; A; P=50%	Compression strength N/mm ²	Gross dry density kg/m ³ D1 (± 10%)
	Length mm	Width mm	Height mm	L mm ±	W mm ±	H mm ±	L mm ±	W mm ±	H mm ±			
Product code												
MRT60	285	85	60	7	4	3	10	6	5	0,34	30	1 440
MRT75	285	85	75	7	4	3	10	6	5	0,34	30	1 450
MRT85	285	85	85	7	4	4	10	6	6	0,34	30	1 460
NRT75	270	130	75	6	5	3	10	7	5	0,34	30	1 470
NRT60	270	130	60	6	5	3	10	7	5	0,34	30	1 460
RT60	285	135	60	7	5	3	10	7	5	0,34	30	1 460
RT75	285	135	75	7	5	4	10	7	5	0,30	30	1 390
RT85	285	135	85	7	5	4	10	7	6	0,34	30	1 490
RT85 piipputiili	277	145	85	6	5	4	10	7	6	0,34	30	1 480
PRT57	257	123	57	6	4	3	10	7	5	0,34	30	1 490
SNF RT62	250	120	62	6	4	3	9	7	5	0,34	30	1 460
ARF RT65	250	120	65	6	4	3	9	7	5	0,34	30	1 460
DNF RT54	228	108	54	6	4	3	9	6	4	0,34	30	1 420

The performance of this product is in accordance with the specifications above	Ylivieska 15.09.2025	 TIILERI
	<i>Ulrika Theqvist</i> Ulrika Theqvist Quality & environmental manager	